
AeroAccess II









Why Buy the AeroAccess II?

- 102" width, low-floor bus
- 4-point kneeling feature
- 6 to 1 ratio auto-deploy & stow ramp
- 19 passengers + driver
- New Standard Federal Foam Headliner
- Exclusive steel reinforced composite construction has superior impact resistance and is free of rust and corrosion
- STAINLESS STEEL entry door frame & stepwell
- Gel-coat exterior is low maintenance and retains its glossy finish
- On-site simulated Altoona test track

Standard Equipment

Chassis

- Deluxe exterior mirror with convex mirror
- · Interior driver rear view mirror

Body

- Heavy duty 12-gauge steel rear wrap around bumper powder coated white to match body
- · Master electric panel easily accessible in operator compartment
- All wiring color, number, and function coded
- All wiring loomed and secured in position with loom ties
- Door-activated interior lights w/driver override
- Steel-reinforced composite body w/5yr, 100K mile warranty
- Bright white, impact resistant, non corrosive, gel-coated, FRP exterior body panels

- Sidewall features 1/4" steel, diagonally reinforced passenger area crash barrier which includes seat mounting track
- Floor frame consists of tubular steel outriggers attached to 11-gauge C-channel mounted on rubber shock isolators
- Trac Lok seat track allows easy seat moving or removal
- 3/4" exterior grade plywood floor undercoated and edge sealed prior to installation
- Stainless steel safety stanchions on each side of the aisle at entry
- Curb side modesty panel with entry assist handrail
- Passenger windows are top T-slide ventilating w/maximum tinting
- All stainless steel powder coated entry door frame and stepwell

Popular Optional Equipment

HVAC

- Passenger A/C ranging from 30,000 to 114,000 BTU
- Passenger heating ranging from 35,000 to 65,000 BTU
- All HVAC systems thermostatically controlled, located in operator compartment

Engine

- (2) Alternators available up to 250 Amp
- Heavy duty battery on stainless slide-out skirt tray

Seating

- Perimeter, forward facing and combination seated floorplans
- Complete range of padded and vandal resistant transit seating

Paratransit

 All necessary equipment for handicapped accessibility and fully compliant with ADA

Comfort, Appearance & Safety

- Deluxe interior trim package
- Custom painting and graphics
- Stainless steel wheel inserts
- Front and side route signs


(Note: This is only a partial listing of optional equipment. For more complete information, contact your ElDorado National representative.)

Chassis Specs & Floorplans


Alternator	Gas: 155 amp
Bumper, front	Chrome
Engine	Gas: 6.8L V-10
Fuel capacity	55 gallon
GVWR	14,500
Suspension	Air Ride
Transmission	Gas: 5-speed
Wheelbase	186"



With our modern 250,000 sq. ft. state-of-the-art facility, we are able to provide timely delivery in addition to the exceptional quality that sets the standard in our industry.



13 Passengers with 3 wheelchair positions



5 Passengers with 2 wheelchair positions







Thor Industries Commercial Bus Division

1655 Wall Street • Salina, KS 67401 (800) 850-1287 • (785) 827-1033 www.enconline.com



At ElDorado National, we constantly improve our product; as a result all specifications and dimensions are subject to change without notice.

